# HD STEEL DOOR SERIES

**Strength** Superior rust inhibition and polyurethane foam core.

Durability Top quality 24-gauge galvanized construction offers superior durability and tested performance.

Security Solid reinforcements ensure that hardware is mounted securely on wood-edge or steel-edge doors.

High Profile Steel Pro® and Steel Mark® doors feature high definition panels in a wide variety of panel designs.

Construction Steel Mark series carry an option of Wood-Edge or Steel-Edge door construction. The Steel Pro series features Wood-Edge door construction.

Fire Ratings 20-minute fire rating options are available on select Steel Mark doors.



Steel Pro® Construction Series



Steel Mark® HD Builder Series



Steel Mark® HD Plus Series



Steel Pro Construction series features 25-gauge steel, wood-edge construction with 13/16" wood stiles and a polyurethane foam core.

Steel Mark HD Builder and Steel Mark HD Plus features 24-gauge steel and offers either steel-edge or wood-edge construction.

All Steel Mark doors feature polyurethane foam cores for superior thermal performance. Wood-edge doors use 1 1/8" wood stiles.



Steel Mark® Wood-Edge and Steel-Edge construction.



### Adjustable Hinge Prep for Steel-Edge Doors

Adjusting the door during normal pre-hanging and installation should not be necessary; as the door leaves the factory with the hinge reinforcements pre-set at correct locations.

During the lifetime of the door it may become necessary to adjust the door due to the normal settling of the house. Having a door with an adjusting hinge feature is perfect for this situation.

## Steel Pro\* Construction Series 6'8"





### **Steel Doors**

	Steel Pro® Construction Series	Steel Mark® HD Builder Series		Steel Mark® HD Plus Entry Series	
Features & Benefits	Wood-Edge	Wood-Edge	Steel-Edge	Wood-Edge	Steel-Edge
Top Quality 24-Gauge Galvanized Construction		•	•	•	•
Primed Surfaces	•	•	•	-	-
Prefinished White Polytex Surface		-	-	•	•
Wood-Edge Construction	•	•	-	•	-
Wood-Edge Construction Featuring Wider Stiles	-	•	-	•	-
Steel-Edge Construction	-	-	•	-	•
12" Wood Lock-Block Reinforcement	•	•	•	•	•
24" Wood Lock-Block Reinforcement**	-	•	•	•	•
Polyurethane Foam Core	•	•	•	•	•
20-Minute Fire Rating Available	-	•	•	•	•
High Definition Panel Profiles	•	•	•	•	•
Adjustable Hinge Prep		-	•	-	•
Warranty	5 years	10 years		20 years	

<sup>\*\*</sup>Standard on 8' doors.

